



**JENFLOW SYSTEMS**  
— EPOXY PLUS —

**Jenflow Systems Ltd**

Unit 17, Old Hall Trading Estate

Bloxwich

Walsall

WS3 3HJ

01922 401 893

mike@jenflow.co.uk

## Underfloor Heating Systems

<b>Compatible?</b>	YES
<b>Screed Depth</b>	Min 10mm
<b>Max Temp</b>	27 Degrees Celsius
<b>Install Temp</b>	18-20 Degrees Celsius
<b>Curing</b>	7 Days (Do Not Exceed 25 Degrees Celsius)
<b>Typical Types</b>	Polypipe Electrical Heating Mats (wet and dry systems)
<b>Consequences of Incorrect Install</b>	Bubbling, Cracks, Burning of Resin (Scorch Effect)



**Prior to install**—Underfloor heating should be switched on for 2 weeks minimum prior to install. If cracks occur repair prior to resin install using Jenflow Rapid Set Grout or Epoxy Grout.

**New Screed**—Slowly increase temp by 5 degrees per day prior to resin install and not exceeding 27 degrees.

For further information contact the Jenflow team on 01922 401 893

Prior to any underfloor heating install we recommend speaking to the underfloor heating manufacture and Jenflow to ensure correct specifications.